Double-Play Aerosol Attachment



ASSEMBLY & USAGE GUIDE

Aerosol Attachment for Streamliner 70 and Streamliner 353





Double-Play | Aerosol Attachment

ATTACHMENT INSTRUCTIONS

3-wheel 353 model and 4-wheel 70 model

The optional Double Play connects to the vertical shaft of the Streamliner handle. If your Streamliner came with the Double Play already attached, skip to **Step 4** for set-up instructions.

- Remove the right handle grip
 on the Streamliner and insert the trigger
 onto the handle shaft. The longest side
 of the triangle shaped trigger should face
 toward the front of the Streamliner
 chalker unit and the small slotted hole
 should be on the bottom. Then, reinstall
 the handle grip.
- **2** To attach Double Play start by unscrewing the tension bolt (red knob) until the end of the bolt is flush with the inside of the unit
- Wrap the Double Play around the vertical handle shaft of the Streamliner so it nestles into the u-joint. The Double Play can be located anywhere on the lower end of the vertical handle shaft.

An adjustment for proper height will be made in *Step 5*. Retighten the tension bolt to hold it to the vertical handle shaft.








- 4 Connect the trigger chain to the trigger on the handle. Slide chain through the larger hole on the trigger and pull the chain taught before locking it into the smaller hole.
- Insert well shaken aerosol field paint can into the Double Play. To properly position the can, make sure the T or H nozzle of the spray can is inserted so that it is perpendicular to the capsule shaped hole in the triggering mechanism below the unit. After properly aligning the can, secure it by pulling the bungee cap up over the can. Place the cap into the concave portion of the base of the spray can. To operate the Double Play, press the trigger on the handle forward with your right thumb or forefinger just enough to spray the paint.
- Set your paint line width by spraying a test on turf that is mowed at the same height as your field turf. Loosen the compression screw and the trigger chain and adjust up or down until your get the desired line width. Remember to adjust the trigger chain length each time the Double Play is moved up or down. Use a permanent marker to indicate the line size. Do this for each size line you will need to paint.









Loosen the compression screw upward for wider lines or downward for narrower lines

Consider these Beacon Built innovative products...

Get the most out of your Streamliner. These innovative accessories will make your routine tasks even easier. Take the imperfection out of creating your softball pitcher's circle with this easy to use kit. After years of operation even a workhorse dry-line marker like the Streamliner can show some wear. This kit with key Streamliner parts provides everything you need to restore your Streamliner to like-new condition.













Get the weight right with either the Beacon X-Drag Kit Field Kit or Adjustable Weight Nail Drag System. Both allow you to adjust the weight with Beacon Field Weights. The correct weight depends upon many factors, and field weights put you in control.

To learn more about our innovative products, visit BeaconAthletics.com/innovation



BeaconAthletics.com | 800-747-5985 | fax 608-836-0724 | Ballfields.com 8233 FORSYTHIA STREET, SUITE 120, MIDDLETON, WI 53562

© Copyright 2017, Beacon Athletics, A division of Rainbow Group, LLC. All Rights reserved. This material may not be republished, rewritten or redistributed including electronically cached without the prior written consent of Beacon Athletics.